

RESILIENCE

SOLVENT ACRYLIC SEALER



BENEFITS:

- Highly durable, long lasting seal
- Enhances the appearance of natural stone and concrete surfaces
- Suitable for use on concrete, terrazzo, slate, granite and most stone surfaces

RESILIENCE is a fast drying, non-yellowing, solvent based acrylic sealer that is suitable for use on internal and external surfaces. RESILIENCE provides a highly durable, long lasting seal that enhances colours and the appearance of natural stone and concrete surfaces, whilst also preventing staining and damage to the substrate. RESILIENCE is suitable for use on concrete, terrazzo, slate, granite, marble and most stone surfaces.

RESILIENCE provides a semi permanent seal that eliminates the need for regular stripping cycles and will last for 2-5 years dependent on environmental wear factors. RESILIENCE also provides a stable base coat for Thermaglo Plus Sealer finish where a buffable finish is required (for Ultra High Gloss).

DIRECTIONS FOR USE:

If using on surfaces other than those listed pretest on a small inconspicuous area prior to widespread application. It is recommended that the test area be monitored for several days to ensure product suitability. Not recommended for use on limestone.

1. If the floor requires removal of an old sealer ensure the floor is stripped and completely dry before applying RESILIENCE to the floor. See technical bulletin for more information.
2. Apply 1-2 coats of RESILIENCE using a Lambs Wool Applicator or Roller. Allow drying time of 30 mins - 3 hours depending on temperature (coat should not be tacky) between coats. It is important to maintain a 'wet edge' on the sealer to avoid leaving marks in the seal. If applying buffable finish leave for 24 hours before application. See technical bulletin for further information.

NOTE: Do NOT allow sealer to contact water until it has fully dried. Do not use on external surfaces if rain is expected within 24 hours.

Resilience - June 2018

SAFETY DATA:

For further information refer to the Safety Data Sheet (SDS) located on our website: www.whiteley.com.au

HEALTH AND SAFETY STATEMENT:

There is no way of predicting an individual's response to cleaning or disinfecting products. All cleaning and disinfecting products have potential to cause skin and other irritation in susceptible individuals. Direct physical contact with the skin should be avoided. If irritation does occur when using this product or any other cleaning/disinfecting solution then the individual should be removed from direct contact with the solution until a satisfactory safe working environment for that individual is determined.

ENVIRONMENTAL STATEMENT:

Whiteley Corporation manufactures products that comply with Australian and International environmental policies. Whiteley Corporation aims to ensure that every product is 100% biodegradable, whilst achieving optimal performance and benefit to customers. All Whiteley Corporation products are supplied in 100% recyclable containers.

Whiteley Corporation and its staff are fully committed to ensuring that our Australian environment and those international environs in which our products are used are enhanced by the use of technology, and that these environments are preserved for the enjoyment of future generations.

© 2018 This document remains property of Whiteley Corporation Pty Ltd.

Alterations are not permitted without prior written authorisation from Whiteley Corporation Pty Ltd.

Resilience - June 2018