


TUNG OIL SEAL

TIMBER SEALER



BENEFITS:

- Sand & Seal in one day
- One-step sealing system
- Burnishable from 400 rpm to 2000+ rpm
- Scuff and mark resistant
- Repairable & patchable
- Slip resistant

TUNG OIL SEAL is an Oleo resinous floor sealer specifically designed to penetrate deeply into the cellulose fibres of wooden floors. TUNG OIL SEAL imparts a tough durable non-slip seal and since it is a penetrative dressing it cannot craze or chip and it resists wear by bonding the structural fibres of the wood. TUNG OIL SEAL is for interior use only.

TUNG OIL SEAL is specifically designed for sealing timber and parquetry floors in halls, gymnasiums, classrooms, offices, showrooms, hotels and restaurants etc. TUNG OIL SEAL conforms to the Australian Standard for the Slip Resistance of Pedestrian Surfaces AS 3661.

WARNING: If applied to timber floors where wax polishes have been previously used, ensure old wax is completely removed by scrubbing the floor with mineral turpentine before using TUNG OIL SEAL. Failure to completely remove wax polishes may cause poor adhesion, peeling and powdering.

DIRECTIONS FOR USE

Preparation:

1. Sand floor with 120 mesh sanding disc. Thoroughly Vacuum and dust mop floor.
2. If a solvent wax polish was previously used, scrub with mineral turpentine diluted at 250mL/L of water. Rinse floor with dilute detergent water and allow to dry.
3. If a water-based wax polish was previously used, scrub floor with XPOLY8. Rinse floor with Citron or Tempo HD and allow to dry.

Tung Oil Seal - March 2009, 1

Application: Apply a liberal coat of TUNG OIL SEAL using a lambs wool applicator taking care to maintain a wet edge. Work well into the surface and level off with an applicator leaving no pooling of the seal. Allow to dry overnight (8 hours minimum). The drying time will vary depending upon the temperature and humidity of the area being sealed. Lightly cut back the first coat with a steel wool or coarse nylon pad. Vacuum thoroughly and apply the second coat. Allow to dry. If the floor has a slightly uneven appearance, lightly cut back again and apply a third coat if necessary.

Please Note: Absorbance rates of wood can vary substantially and as a result some older timber surfaces may require more coats of TUNG OIL SEAL than recommended.

Maintenance: Allow 24 to 48 hours drying. Apply either Timberglo or Thermaglo Plus. Refer to the specific technical bulletin for advice on these alternatives.

SAFETY DATA

For further information refer to the Material Safety Data Sheet (MSDS) located on the Whiteley Industrial web site: www.whiteley.com.au

HEALTH AND SAFETY STATEMENT

There is no way of predicting an individual's response to cleaning or disinfecting products. All cleaning and disinfecting products have potential to cause skin and other irritation in susceptible individuals. Direct physical contact with the skin should be avoided. If irritation does occur when using this product or any other cleaning/disinfecting solution then the individual should be removed from direct contact with the solution until a satisfactory safe working environment for that individual is determined.

ENVIRONMENTAL STATEMENT

Whiteley Industrial manufactures products that comply with Australian and International environmental policy. Whiteley Industrial aims to ensure that every product is 100% biodegradable, whilst achieving optimal performance and benefit to customers. All Whiteley Industrial products are supplied in 100% recyclable containers.

Whiteley Industrial and its staff are fully committed to ensuring that our Australian environment and those international environs in which our products are used are enhanced by the use of technology, and that these environments are preserved for the enjoyment of future generations.

© 2013 This document remains property of Whiteley Corporation Pty Ltd. Alterations are not permitted without prior written authorisation from Whiteley Corporation Pty Ltd.

Tung Oil Seal - March 2009, 2